

## Specifications

### DTP3 R 201

#### TRUE 4K specification

Max. 4K Capabilities		
Resolution and Refresh Rate	Chroma Sampling	Max. Bit Depth per Color
4096 x 2160 at 60 Hz	4:4:4	8 bit
3840 x 2160 at 60 Hz		
4096 x 2160 at 30 Hz		12 bit
3840 x 2160 at 30 Hz		
4096 x 2160 at 60 Hz	4:2:0	
3840 x 2160 at 60 Hz		

Frame rate<sup>1</sup> ..... 24, 25, 30, 50, or 60 fps  
 Chroma sampling<sup>1</sup> ..... 4:4:4, 4:2:2, or 4:2:0  
 Color bit depth<sup>1</sup> ..... 8, 10, 12 bits per color  
 Signal type ..... HDMI 1.x/2.0b, HDCP 2.3  
 Max. video data rate ..... 18 Gbps (6 Gbps per color)

**NOTE:** <sup>1</sup>Subject to the maximum data rate limit. Use our calculator at [www.extron.com/8KdataRate](http://www.extron.com/8KdataRate) to determine video parameters supported by this data rate.

#### Video

Maximum data rate ..... 18 Gbps (6 Gbps per color)  
 Maximum pixel clock ..... 600 MHz  
 Resolution range ..... Up to 1080p @120 Hz or 4K @60 Hz (4:4:4 chroma subsampling)  
 Horizontal frequency range ..... 15 kHz to 270 kHz for resolutions up to 18 Gbps  
 Vertical frequency range ..... 24 Hz to 240 Hz for resolutions up to 18 Gbps  
 Color bit depth ..... 8, 10, or 12 bits — subject to the maximum data rate limit  
 Formats ..... RGB and YCbCr digital video  
 HDR ..... HDR10, HDR10+, Dolby Vision  
 Standard ..... HDMI 2.0b, DVI 1.0, HDCP 1.x, HDCP 2.3, CTA-861-F

**NOTE:** Extron strongly recommends compatibility testing while designing, and before installing, any HDR system. There are several HDR formats in use by source and display manufacturers. The level of HDR product support is governed by pixel clock, signal format, and signal communication between source and sink devices. Please contact an Extron Application Engineer for more information.

#### Video input

Number/signal type  
     DTP3 ..... 1 DTP3  
 Connector  
     DTP3 input ..... 1 female RJ-45 jack

## Specifications • DTP3 R 201 (Continued)

### Interconnection between transmitter and receiver

Connector.....	1 female RJ-45 per unit
Termination standard.....	TIA/EIA T568B
Signal transmission distance.....	Up to 330' (100 m) using CAT 6A shielded twisted pair (STP) cable
Cable requirements.....	Solid conductor, 22 AWG or better
Cable recommendations.....	500 MHz bandwidth, STP (shielded twisted pair)

### Video output

Number/signal type.....	1 single link HDMI (or DVI-D*)
Connectors.....	1 female HDMI

**NOTE:** \*Appropriate HDMI to DVI-D cables or adapters are required for DVI signal input/output.

### Audio output – analog

Number/signal type.....	1 stereo, balanced/unbalanced (fixed and variable outputs) 1 analog audio and 1 embedded digital audio on HDMI
Connectors.....	(1) 3.5 mm captive screw connectors, 5-pole 1 female HDMI type A
Impedance.....	50 ohms unbalanced, 100 ohms balanced
Gain error.....	±0.5 dB channel to channel
Maximum level (Hi-Z).....	>+21 dBu, balanced; >+15 dBu, unbalanced

**NOTE:** 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV ≈ 2 dBu

### Control/remote – external device (RS-232 Over TP)

Serial control pass-through ports ...	(1) RS-232 3.5 mm 3-pole captive screw connector
Baud rate.....	300 to 115 k baud,
Protocol.....	8 or 7 data bits 1 or 2 stop bits No parity (default), even or odd parity
Serial control pin configuration .....	1 = Tx, 2 = Rx, 3 = GND

**NOTE:** Protocol is mirrored between the connected DTP3 Rx endpoints and the "Over TP". Signals from a control device pass into each "Over TP" port, are embedded with the DTP signal, and sent to the individual DTP3 endpoints for control of remote sink or source devices. The "Over TP" ports are simply pass-through connections to DTP endpoints. There is no RS-232 insertion from any DTP3 control port to the "Over TP" ports.

### Control/remote

USB control port.....	1 front panel female USB-C
USB standards .....	USB 2.0, low speed
Program control.....	Extron Simple Instruction Set (SIS), Extron Product Configuration Software (PCS)

# Specifications • DTP3 R 201 (Continued)

## General

Power supply .....	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 1.5 A, 18 watts
Power consumption	
Device .....	TBD watts, 12 VDC
Device and power supply .....	TBD watts, 100-240 VAC, 50-60 Hz

**NOTE:** The receiver can be powered either locally by an external power supply or remotely by a transmitter on the other end of the twisted pair cable.

Temperature/humidity .....	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling .....	Convection, vents on top and sides
Thermal dissipation	
Device .....	TBD BTU/hr
Device and power supply .....	TBD BTU/hr
Mounting	
Rack mount.....	Yes, with optional 1U high rack shelf
Furniture mount .....	Yes, with optional under-desk mounting kit
Enclosure type .....	Metal
Enclosure dimensions .....	1.0" H x 4.3" W x 6.0" D (quarter rack wide) (2.5 cm H x 10.9 cm W x 15.2 cm D) (Depth excludes connectors.)
Product weight .....	TBD lbs (TBD kg)
Regulatory compliance.....	CE, C-tick, C-UL, UL, FCC Class A, ICES, VCCI
Product warranty .....	3 years parts and labor
Everlast power supply warranty.....	7 years parts and labor

**NOTE:** All nominal levels are at ±10%.

**NOTE:** Specifications are subject to change without notice.

**NOTE:** Shipping weights and dimensions are available at [www.extron.com](http://www.extron.com).

5252-D1