

KT-HD40 Series



Selling Point:

1. 1080P HD resolution, 12X/20X optical zoom, support close-up snapshots at a long distance
2. Support USB 2.0 plug-and-play, adapt to various conference and video applications
3. HDMI mainstream interface, can support the docking and matching of mainstream devices
4. 355-degree rotating pan/tilt, can capture multi-angle video
5. Compatible with SONY VISCA protocol and PELCO P/D protocol
6. Support image flip (suitable for desktop and ceiling installation)

Parameters:

Item No.	KT-HD40R	KT-HD40A
Image Sensor	SONY 1/2.8 Progressive CMOS	
Effective Pixels	3.10 Megapixels	3.50 Megapixels
Resolution	U2:MJPEG/H.264:320*240,640*480,800*600,1280*720,1920*1080	
	HDMI:1080P60/50,1080P30/25,1080i60/50,720P60/50	
Signal System	PAL/NTSC	
Lens	12X optical zoom f=3.9mm(w)~46.8 mm(f) F1.8~F2.8	20X optical zoom f=4.7mm(w)~94.0 mm(f) F1.6~F2.8
Horizontal View Angle	72.5°(W)~7.4°(T)	58.7°(W)~3.2°(T)
Focus System	Auto/Manual	
Minimum Illumination	0.1 Lux	
Shutter Speed	1/1~1/10000S	
Gain	Auto/Manual	
White Balance	Auto/Manual/Indoor/Outdoor	
Image Effect	Full color/black and white/Electronic flip	
S/N Ratio	≥50db	
Pan	355°(max. speed:80°/s)	
Tilt	- 30° to +90° (max. speed: 60°/s)	
Preset Position	9 preset positions by IR remote controller,	
Video Output HD	HDMI、USB 2.0	
Power	12V DC(10.8~13.0V DC)	
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~60°C	
Dimension	(L)181×(W)181×(H)176mm	
Consumption	Max.12W (DC 12V)	
Weight	1525g	
Color	Silver	
Control Protocol	SONY VISCA, PELCO P/D	
Control Mode	RS-232/485/USB Control	
Accessories	DC 12V power adapter, IR Remote, Operation manual, HDMI Cable, USB cable, RS-232 cable, Ceiling bracket	