

KT-HD40 HD Series



Selling Point:

1. 1080P full HD resolution, 12x/20x optical zoom, support close-up snapshots at a long distance
2. Support 3G-SDI, HDMI and IP, adapt to various conference and video applications
3. HDMI mainstream interface, support the docking and matching of mainstream devices
4. 355-degree rotating pan/tilt, can capture multi-angle video
5. 72.5° / 58.7° wide angle lens, meet the demand of large view even in small room
6. Compatible with SONY VISCA protocol and PELCO P/D protocol
7. Support image flip (suitable for desktop and ceiling installation)

Parameters:

Product name	KT-HD40RS	KT-HD40AS
Image Sensor	SONY 1/2.8" Progressive CMOS	
White Balance	3.10 Megapixels	3.50 Megapixels
Image Effect	1080P60/50, 1080P30/25, 1080i60/50, 720P60/50	
	Optional: 1080p59.94, 1080p29.97, 1080i59.94	
Signal System	PAL/NTSC	
Lens	12X zoom optional f=3.9mm(wide angle end) ~ 46.8mm(far end)	20X zoom optional f=4.7mm(wide angle end) ~ 94.0mm(far end)
	Horizontal View Angle	72.5°(W)~7.4°(T)
Focus System	Auto/Manual	
Minimum Illumination	0.1 Lux	
Shutter Speed	1/1~1/10000S	
Gain	Auto/Manual	
White Balance	Auto/Manual/Indoor/Outdoor	
Image Effect	Full color//Electronic flip	
S/N Ratio	≥50db	
Pan	355°(max. speed:80°/s)	
Tilt	- 30° to +90° (max. speed: 60°/s)	
Preset Position	9 preset positions by IR remote controller	
Video Output HD	HDMI, 3G/HD-SDI, IP	
Control Mode	RS-232C, RS-422/485	
Power	12V DC(10.8~13.0V DC)	
Operating Temperature	0°C~40°C	
Storage Temperature	-20°C~60°C	
Dimension	(L)181×(W)181×(H)176mm	
Consumption	Max.12W (DC 12V)	
Weight	1525g	
Color	Silver	
Control Protocol	SONY VISCA、PELCO P/D	
Network protocol	VISCA over IP, RTSP, RTMP, ONVIF	
Control Mode	RS-232C, RS-422/485	
Accessories	DC 12V power adapter, IR Remote, Operation manual, RS-232C Cable, HDMI cable, Ceiling bracket	
Carton	Each camera in a small carton, then 4 pcs packaged in one large carton	
Certificate	ISO/CE/FCC/RoHS	
Warranty	3 years	